



SAFETY DATA SHEET

TA26

Page: 1

Compilation date: 27/11/2009

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: A0026

REACH registered number(s): 01-2119471310-51,01-2119484651-34,01-2119471330-49

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Adhesive.

1.3. Details of the supplier of the safety data sheet

Company name: Tunnelling Accessories

Churchfields Industrial Estate

Sidney Little Road

St Leonards On Sea

TN38 9PU

United Kingdom

Tel: 01424854112

Fax: 01424 854231

Email: info@tunnellingaccessories.co.uk

1.4. Emergency telephone number

Emergency tel: 01827 69662

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xi: R36/38; Xn: R48/20; -: R52/53; Xn: R63; -: R66; -: R67

Classification under CLP: Eye Irrit. 2: H319; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336

Most important adverse effects: Highly flammable. Irritating to eyes and skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Possible risk of harm to the unborn child. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

2.2. Label elements

Label elements under CLP:

Hazard statements: H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

[cont...]

SAFETY DATA SHEET

TA26

Page: 2

H336: May cause drowsiness or dizziness.

H361d: Suspected of damaging the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard



Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.

Rinse skin with water/shower.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P501: Dispose of contents/container to specialised waste company.

Label elements under CHIP:

Hazard symbols: Highly flammable.

Harmful.



Risk phrases: R11: Highly flammable.

R36/38: Irritating to eyes and skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R63: Possible risk of harm to the unborn child.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S9: Keep container in a well-ventilated place.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe vapour.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S24/25: Avoid contact with skin and eyes.

S36/37: Wear suitable protective clothing and gloves.

S29/35: Do not empty into drains; dispose of this material and its container in a safe way.

Precautionary phrases: Restricted to professional users.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

[cont...]

SAFETY DATA SHEET

TA26

Page: 3

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TOLUENE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
203-625-9	108-88-3	F: R11; Xi: R38; Xn: R48/20; Xn: R63; Xn: R65; -: R67	Flam. Liq. 2: H225; Repr. 2: H361d; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336	30-50%

ACETONE

200-662-2	67-64-1	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%
-----------	---------	---------------------------------	--	--------

LOW BOILING POINT NAPHTHA - UNSPECIFIED - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED LIGHT, DEAROMATIZE

295-434-2	92045-53-9	Xn: R65; F+: R12; Xi: R38; N: R51/53	Asp. Tox. 1: H304; Flam. Liq. 1: H224; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	10-30%
-----------	------------	--------------------------------------	---	--------

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED LIGHT

265-151-9	64742-49-0	Xn: R65; F+: R12; Xi: R38; N: R51/53	Asp. Tox. 1: H304; Flam. Liq. 1: H224; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	10-30%
-----------	------------	--------------------------------------	---	--------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact:

Remove from skin with paper or towel. Wash effected area thoroughly with soap and water. Seek medical advice if symptoms persist.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor if symptoms persist.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

[cont...]

SAFETY DATA SHEET

TA26

Page: 4

Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

[cont...]

SAFETY DATA SHEET

TA26

Page: 5

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	191 mg/m3	574 mg/m3	-	-

Hazardous ingredients:

TOLUENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	191 mg/m3	384 mg/m3	-	-

ACETONE

UK	1210 mg/m3	3620 mg/m3	-	-
----	------------	------------	---	---

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

Hand protection: Avoid skin contact. For repeated exposure use Viton or 4H chemical gloves. the user must COSHH risk assess to determine the correct glove.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Cream

Odour: Characteristic odour

Evaporation rate: Fast

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Viscous

Boiling point/range°C: 56

upper: 13

Autoflammability°C: 200

Flammability limits %: lower: 0.6

Flash point°C: -35

Relative density: 0.85

9.2. Other information

Other information: Not applicable.

[cont...]

SAFETY DATA SHEET

TA26

Page: 6

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg
VAPOURS	RAT	4H LC50	>5	mg/l

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated
Repeated dose toxicity	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
---------	------	-------	-------

[cont...]

SAFETY DATA SHEET

TA26

Page: 7

ALGAE	48H EC50	1-10	mg/l
FISH	96H LC50	1-10	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable in part only.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Wet waste: Arrange for disposal by a licenced waste disposal company

Disposal of packaging: Arrange for disposal by a licenced waste disposal company

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

Shipping name: ADHESIVES

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: This product is classified as a mixture. CLP classification for information only.

[cont...]

SAFETY DATA SHEET

TA26

Page: 8

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This Safety Data Sheet is compliant with the Chemical [Hazard Information and

Phrases used in s.2 and 3:

Packaging for Supply] Regulations 2002

EUH066: Repeated exposure may cause skin dryness or cracking.

H224: Extremely flammable liquid and vapour.

H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H350: May cause cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>. H361d: Suspected of damaging the unborn child.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

R11: Highly flammable.

R12: Extremely flammable.

R36/38: Irritating to eyes and skin.

R36: Irritating to eyes.

R38: Irritating to skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the

[cont...]

SAFETY DATA SHEET

A0026

Page: 9

aquatic environment.

R63: Possible risk of harm to the unborn child.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.