

DIAMOND SEAL ®

Absorbent Polymer for Lost Circulation

Description

DIAMOND SEAL is a water-swellable but not water-soluble, 100% crystalline synthetic polymer. DIAMOND SEAL absorbs hundreds of times its own weight in water. It is intended for use primarily as a lost circulation material for horizontal directional drilling.

Applications/Functions

- Lost circulation material for horizontal directional drilling
- Prevent inadvertent returns in river crossing applications
- · Stabilize borehole in cobble and gravel
- Stabilize unconsolidated formations

Advantages

- Rapid water absorption
- · Effective in mitigating lost circulation
- Economical small quantity yields large volume
- Easy to use
- Non-fermenting

Typical Properties

Appearance off-white free-flowing crystals

Specific gravity 0.75

Dry screen analysis
 96% through 5 mesh (4.0 mm)

Swelling capacity in fresh water 3.5 ft³/lb (0.22 m³/kg)

Recommended Treatment

For slug treatment:

Add 1/2 to 1 pound (0.25-0.5 kg) DIAMOND SEAL per joint

As a pill:

- Add DIAMOND SEAL at 10 20 lb/100 gallons of drilling fluid
- Add DIAMOND SEAL at 12 24 kg/m³ of drilling fluid

Treatment for Loss of Circulation or Inadvertent Returns in HDD Operations:

(Prior to pumping remove all in-line screens in circulating system) Add the following to existing drilling fluid and displace:

BAROLIFTTM - $0.25 - 0.5 \text{ lb}/100 \text{ gallons} (0.3 - 0.6 \text{ kg/m}^3)$

N-SEALTM - 3 - 5 lb/100 gallons (3.6 - 6.0 kg/m³)
DIAMOND SEAL - 10 - 20 lb/100 gallons (12 - 24 kg/m³)

© Copyright 2001 Baroid, a Halliburton PSL

Rev. 6/2001 · IDP 052

Packaging

DIAMOND SEAL® is packaged in 10-lb (4.5-kg) resealable plastic containers.

Availability

DIAMOND SEAL can be purchased through any Baroid Industrial Drilling Products Distributor. To locate the Baroid IDP distributor nearest you contact the Customer Service Department in Houston or your area IDP Sales Representative.

Baroid Industrial Drilling Products,

A Product and Service Line of Halliburton Energy Services, Inc.

3000 N. Sam Houston Pkwy E.

Houston, TX 77032

Customer Service (800) 735-6075 Toll Free (281) 871-4612

Technical Service (877) 379-7412 Toll Free (281) 871-4613