

PENETROL[®] EU

Wetting Agent

Description	PENETROL [®] EU Wetting Agent is a water miscible, non-ionic surfactant designed to counteract the sticking tendencies of clay.		
Applications/Functions	 The use of PENETROL EU Wetting Agent aids the following: Reduce or eliminate bit balling Reduce surface tension of drilling fluid, which allows faster chip removal without continuously grinding the hard shale formations Improve drilling efficiency by preferentially coating the bottom-hole assembly and drill string Minimize differential sticking Increase bit life and reduce drill pipe and bottom-hole assembly wear 		
Advantages	Easy to mix Effective in low concentrations Compatible with other Baroid IDP drilling fluid additives Biodegradable		
Typical Properties	 Appearance Specific gravity pH Flash point, TOC, °C, °F 	green liquid ~1 10 >100 °C, >212 °F	
Recommended	Added uniformly through entire circulation system		
Treatment	2.5 to 10 liters of PENETROL EU Wetting Agent per m ³ of drilling fluid		
	 1 to 4 quarts of PENETROL EU Wetting Agent per 100 gallons of drilling fluid 		
	As a slug down drill rods to counteract the sticking tendencies of clay		
	1 to 2 liters of PENETROL EI	1 to 2 liters of PENETROL EU Wetting Agent per drill rod	
	 1 to 2 quarts of PENETROL EU Wetting Agent per drill rod 		
	Alternate application		
		Dilute 3.8 liters of PENETROL EU Wetting Agent with 38 liters of water and inject 3.8 liters of mixture per minute into the pump suction	
	Dilute 1 gallon of PENETROL EU Wetting Agent with 10 gallons of water and inject one gallon of mixture per minute into the pump suction		

© Copyright 2020 Halliburton PENETROL is a registered trademark of Halliburton

Rev. 03/2020

Because the conditions of use of this product are beyond the seller's control, the product is sold without warranty either express or implied and upon condition that purchaser make its own test to determine the suitability for purchaser's application. Purchaser assumes all risk of use and handling of this product. This product will be replaced if defective in manufacture or packaging or if damaged. Except for such replacement, seller is not liable for any damages caused by this product or its use. The statements and recommendations made herein are believed to be accurate. No guarantee of their accuracy is made, however.

Packaging PENETROL[®] EU Wetting Agent is packaged in 20 Liter Drum.

Availability PENETROL EU Wetting Agent can be purchased through any Baroid Industrial Drilling Products Retailer. To locate the Baroid IDP retailer nearest you contact the Customer Service Department or your area IDP Sales Representative.

> CEBO Holland, BV Authorized Retailer, Baroid IDP Westerduinweg 1 NL-1976 BV IJmuiden Customer Service __+31 (0)255-546262

© Copyright 2020 Halliburton PENETROL is a registered trademark of Halliburton

Rev. 03/2020 · IDP 050

Because the conditions of use of this product are beyond the seller's control, the product is sold without warranty either express or implied and upon condition that purchaser make its own test to determine the suitability for purchaser's application. Purchaser assumes all risk of use and handling of this product. This product will be replaced if defective in manufacture or packaging or if damaged. Except for such replacement, seller is not liable for any damages caused by this product or its use. The statements and recommendations made herein are believed to be accurate. No guarantee of their accuracy is made, however.