

PENETROL[®] DRY EU

Surfactant

Description	PENETROL [®] DRY EU surfactant is used to assist in counteracting the sticking tendencies of encountered clay or shale during drilling operations.
Applications/Functions	The use of PENETROL DRY EU surfactant aids or promotes the following:
	 Reduces and/or minimizes bit balling Improves drilling efficiency by preferentially coating the bottom-hole assembly and drill string Minimizes potential for accretion and agglomeration of cuttings
Advantages	 Free-flowing granular product Easy to mix and readily dispersible Effective at low concentrations Minimal to no foaming produced during high shear mixing or surface agitation Compatible with other Baroid drilling fluid additives Low aquatic toxicity
Typical Properties	 Appearance Bulk Density, lb/ft³, kg/m³ pH (1.0% Aqueous Solution) White granules 40 - 45, 641 - 721 6.5
Recommended Treatment	Approximate Amounts of PENETROL DRY EU Surfactant Added to Water Based Fluids, kg/m ³
	0.6 - 3.6
	*1 bbl = 42 U.S. gallons or 0.16 m^3
	 It is recommended that Soda Ash (sodium carbonate) be added to the make-up water prior to the addition of PENETROL DRY EU surfactant for reduction of excess calcium and pH adjustment. Introduction of PENETROL DRY EU surfactant requires the user to incorporate the material into the drilling fluid system using a venturi hopper or directly into the vortex of a high-speed stirrer and follow standard order of addition. PENETROL DRY EU should be incorporated only after bentonite and/or polymers have been mixed and fully hydrated. The above are generalized concentrations of PENETROL DRY EU surfactant to be added to water-based drilling fluids. The ultimate usage concentration will be based on local geology, application and mixing efficiency. In the event that further information is needed please refer to the Product Data Sheet or contact your local Baroid IDP representative.
Packaging	PENETROL DRY EU surfactant is packaged in 9 kg re-sealable plastic pails.
Availability	PENETROL DRY EU surfactant is a regionally sourced product and may not be available through all Baroid Industrial Drilling Products Retailers. To locate the Baroid IDP retailer nearest you contact CEBO Holland
	CEBO Holland, BV
	Authorized Retailer, Baroid IDP
	Westerduinweg 1
	C C
	NL-1976 BV ljmuiden Customer Service: +31 (0)255-546262

 $^{\odot}$ Copyright 2019 Halliburton PENETROL $^{\otimes}$ is a registered trademark of Halliburton

Because the conditions of use of this product are beyond the seller's control, the product is sold without warranty either express or implied and upon condition that purchaser make its own test to determine the suitability for purchaser's application. Purchaser assumes all risk of use and handling of this product. This product will be replaced if defective in manufacture or packaging or if damaged. Except for such replacement, seller is not liable for any damages caused by this product or its use. The statements and recommendations made herein are believed to be accurate. No guarantee of their accuracy is made, however.