

TUNNEL-GEL® PLUS

Viscosifier/Gellant

Description

TUNNEL-GEL[®] PLUS viscosifier is a specially formulated, high-yield bentonite designed for use in tunneling and large diameter HDD operations. TUNNEL-GEL PLUS viscosifier promotes rapid viscosity development while maintaining effective borehole stabilization and enhanced filtration control in most water-based drilling fluids.

Applications/Functions

The use of TUNNEL-GEL PLUS viscosifier assists and promotes the following:

- Enhanced viscosity development in freshwater drilling fluids
- Effective cuttings transport and suspension characteristics
- Enhanced filtration control and resulting borehole stability
- Effective lubrication fluid for microtunneling operations

Advantages

- Easy to mix and quickly reaches maximum viscosity
- Enhances fluid lubricity for reduction of required jacking forces
- Yields more than twice as much drilling fluid of the same viscosity as an equal concentration of API grade bentonite

Typical Properties

	Appearance	Yellow to tan powder
•	Specific gravity, g/cm ³	2.6

pH (3% Solution)

Recommended Treatment

To optimize the yield and performance of TUNNEL-GEL PLUS viscosifier, pretreat make-up water with soda ash (sodium carbonate) at a concentration of 0.5 – 1.0 kg/m³ to reduce excess calcium hardness to ≤100 mg/l and adjust pH to a range between 8.5 – 9.5.

10.4

 Using a Venturi hopper, or a colloidal mixer, add TUNNEL-GEL PLUS viscosifier, slowly and uniformly to the entire circulating system or mix tank.

Approximate Amounts of TUNNEL-GEL PLUS viscosifier Added to Water Based Fluids				
lbs/bbl	lbs/100gallons	kg/m³		
8.4 – 12.6	20 – 30	25 – 35		

Packaging

TUNNEL-GEL PLUS viscosifier, is packaged in 25-kg (55.1-lb) multiwall paper bags.

Availability

TUNNEL-GEL PLUS viscosifier, can only be purchased through European Baroid Industrial Drilling Products Retailers. To locate the Baroid IDP retailer nearest you contact the Customer Service Department in Houston or your area IDP Sales Representative.

Baroid Industrial Drilling Products Product Service Line, Halliburton

3000 N. Sam Houston Pkwy. E. Houston, TX 77032

Customer Service	(800) 735-6075 Toll Free	(281) 871-4612
Technical Service	(877) 379-7412 Toll Free	(281) 871-4613